

# LAMIGLAZER A2 Semi-Auto

**hilton**  
laminating

The NEW LG A2 (semi-automatic) system, provides the perfect solution for economical mid-volume, high quality single side lamination of book covers, brochures, magazine covers, business cards and more. Semi-automatic feeding Automatic laminating and separating. Laminator for Digital Printing, operated by pneumatic system.

- Maximum 12.0m/min Laminating speed provides high productivity.
- Large chrome plated heat roller increases thermal capacity.
- Infrared temperature sensor and CPU control system enables reliable control.
- Pneumatic System provides accurate overlapping, nip pressure and bursting.
- Adjustable decurling device with cooling blowers ensure flat sheets.
- Both sides opened film shaft eases film loading.
- In-line film splitter and perforator allows film for any sheet size.
- Job sheet counter tracks usage.



LAMINATING SPEED	Up to 12.0/min
LAMINATING WIDTH	620mm
MAX NIP OPENING	20mm
MAX WORKING TEMPERATURE	150 C
WARM UP TIME	About 15mins
LAMINATING FILMS	BOPP
TYPE OF PAPER	120-350 gsm
FILM CORE SIZE	76mm
CONTROL SYSTEM	Infrared temp sensor & 8-bit CPU control
HEATING SYSTEM	Hot Roller Internal Infrared
COOLING SYSTEM	5 Speed cooling fans
ROLLER LIFT-UP SYSTEM	Pneumatic
PNEUMATIC WORKING PRESSURE	0.6 MPa
POWER REQUIREMENTS	AC220OV-240V, 50/60Hz
POWER CONSUMPTION	1700W, 8A
DIMENSIONS (LXWXH)	1420 (L) x 963 (W) x 1470 (H)mm(with stand).
MACHINE WEIGHT	210 Kgs

**hilton**  
laminating

 **1800 819 970**

26 Stephen Rd, Dandenong South Vic 3175 Australia  
[www.hiltonlaminating.com.au](http://www.hiltonlaminating.com.au)